

AUXILIARY PARTS-SHAFT THREAD AND KEYWAY DIMENSIONS FOR STANDARD LOCKNUTS, LOCKWASHERS AND TONGUED WASHERS



ABMA Locknut Number	Number Per Inch	Threads(in.)									Shaft Ext. Dia.(in.) V ₂ Max.	Thread Length(in.) +0.016 -0.000			Keyway(in.)			
		Major Diameter			Pitch Diameter ⁽¹⁾			Minor Diameter Max.	Relief Diameter A	Relief Width +0.016-0.000 Br		+0.016 -0.000 L ₁	+0.016 -0.000 L ₂	Depth Max. X	Width S ⁽²⁾	M ⁽²⁾	U ⁽²⁾	
		Max.	Tol.	Min.	Max.	Tol.	Min.											
N-00	32	0.391	0.0054	0.3856	0.3707	0.0026	0.3681	0.3257	0.3371 ± 0.005	0.062	0.312	0.593	0.375	0.287	0.125	0.094	0.469	
N-01	32	0.469	0.0054	0.4636	0.4487	0.0026	0.4461	0.4307	0.4151 ± 0.005	0.062	0.406	0.781	0.468	0.366	0.125	0.094	0.562	
N-02	32	0.586	0.0054	0.5806	0.5657	0.003	0.5627	0.5477	0.5321 ± 0.005	0.062	0.5	0.812	0.5	0.485	0.125	0.094	0.594	
N-03	32	0.664	0.0054	0.6586	0.6437	0.003	0.6407	0.6257	0.6101 ± 0.005	0.062	0.562	0.875	0.531	0.564	0.125	0.094	0.625	
N-04	32	0.781	0.0054	0.7756	0.7607	0.0034	0.7573	0.7427	0.7271 ± 0.005	0.062	0.703	0.906	0.531	0.676	0.188	0.094	0.625	
N-05	32	0.969	0.0054	0.9636	0.9487	0.0034	0.9453	0.9307	0.9151 ± 0.005	0.062	0.875	1	0.593	0.835	0.188	0.125	0.719	
N-06	18	1.173	0.0082	1.1648	1.1369	0.004	1.1329	1.1048	1.0892 ± 0.005	0.093	1.062	1	0.593	1.04	0.188	0.125	0.719	
TN-065	18	1.312	0.0082	1.3043	1.2764	0.004	1.2724	1.2443	1.2287 ± 0.005	0.093	1.188	1.062	0.625	1.18	0.188	0.125	0.75	
TN-07	18	1.376	0.0082	1.3678	1.3399	0.004	1.3359	1.3078	1.2922 ± 0.005	0.093	1.25	1.062	0.625	1.244	0.188	0.125	0.75	
TN-08	18	1.563	0.0082	1.5548	1.5269	0.0045	1.5224	1.4948	1.4792 ± 0.005	0.093	1.438	1.062	0.625	1.422	0.312	0.125	0.75	
TN-09	18	1.767	0.0082	1.7588	1.7309	0.0045	1.7264	1.6988	1.6832 ± 0.005	0.125	1.656	1.062	0.625	1.628	0.312	0.156	0.781	
TN-10	18	1.967	0.0082	1.9588	1.9309	0.0045	1.9264	1.8988	1.8832 ± 0.005	0.125	1.859	1.187	0.687	1.83	0.312	0.156	0.844	
TN-11	18	2.157	0.0082	2.1488	2.1209	0.0051	2.1158	2.0888	2.0732 ± 0.005	0.125	2.047	1.187	0.687	2.021	0.312	0.156	0.844	
TN-12	18	2.36	0.0082	2.3518	2.3239	0.0051	2.3188	2.2918	2.2762 ± 0.005	0.125	2.25	1.281	0.75	2.194	0.312	0.156	0.906	
TN-13	18	2.548	0.0082	2.5398	2.5119	0.0051	2.5068	2.4798	2.4642 ± 0.005	0.125	2.422	1.343	0.781	2.382	0.312	0.156	0.938	
TN-14	18	2.751	0.0082	2.7428	2.7149	0.0051	2.7098	2.6828	2.6672 ± 0.005	0.125	2.625	1.343	0.781	2.586	0.312	0.25	1	
TAN-15	12	2.933	0.0112	2.9218	2.8789	0.0054	2.8735	2.8308	2.7995 ± '0.010	0.156	2.781	1.406	0.812	2.737	0.312	0.25	1.031	
TAN-16	12	3.137	0.0112	3.1258	3.0829	0.0059	3.077	3.0348	3.0035 ± 0.010	0.156	3	1.406	0.812	2.938	0.375	0.25	1.031	
TAN-17	12	3.34	0.0112	3.3288	3.2859	0.0059	3.28	3.2378	3.2065 ± 0.010	0.156	3.188	1.468	0.843	3.141	0.375	0.25	1.062	
TAN-18	12	3.527	0.0112	3.5158	3.4729	0.0074	3.4655	3.4248	3.3935 ± 0.010	0.156	3.375	1.625	0.937	3.298	0.375	0.25	1.156	
TAN-19	12	3.73	0.0112	3.7188	3.6759	0.0074	3.6685	3.6278	3.5965 ± 0.010	0.156	3.562	1.687	0.968	3.502	0.375	0.25	1.188	
TAN-20	12	3.918	0.0112	3.9068	3.8639	0.0074	3.8565	3.8158	3.7845 ± 0.010	0.156	3.766	1.75	1	3.69	0.375	0.312	1.281	
TAN-21	12	4.122	0.0112	4.1108	4.0679	0.0083	4.0596	4.0198	3.9885 ± 0.010	0.156	3.938	1.75	1	3.894	0.375	0.312	1.281	
TAN-22	12	4.325	0.0112	4.3138	4.2709	0.0083	4.2626	4.2228	4.1915 ± 0.010	0.156	4.156	1.812	1.031	4.098	0.375	0.312	1.312	
TAN-24	12	4.716	0.0112	4.7048	4.6619	0.0083	4.6536	4.6138	4.5825 ± 0.010	0.156	4.531	1.906	1.093	4.458	0.375	0.312	1.375	
TAN-26	12	5.106	0.0112	5.0948	5.0519	0.0083	5.0436	5.0038	4.9725 ± 0.010	0.156	4.906	2.031	1.156	4.844	0.5	0.312	1.438	
TAN-128	12	5.497	0.0112	5.4858	5.4429	0.0083	5.4346	5.3948	5.3635 ± 0.010	0.156	5.297	2.656	1.468	5.229	0.625	0.312	1.75	
TAN-130	12	5.888	0.01125	5.8768	5.8339	0.0083	5.8256	5.7858	5.7545 ± 0.010	0.156	5.656	2.812	1.562	5.59	0.625	0.375	1.906	
TAN-132	8	6.284	0.0152	6.2688	6.2028	0.0091	6.1937	6.1306	6.0993 ± 0.010	0.25	6.062	2.875	1.593	5.956	0.625	0.375	1.938	

AUXILIARY PARTS-SHAFT THREAD AND KEYWAY DIMENSIONS FOR
STANDARD LOCKNUTS, LOCKWASHERS AND TONGUED WASHERS

TAN-134	8	6.659	0.0152	6.6438	6.5778	0.0091	6.5687	6.5056	0.4743 ± 0.010	0.25	6.438	3	1.656	6.326	0.75	0.375	2