

Double Row Full Complement Cylindrical Roller Bearings

| Bearing NO. | Граничные размеры (мм) | | | | | Номинальная грузоподъемность (кН) | | Limiting speed(rpm) | | Abutment and fillet dimensions(mm) | | | Weight (kg) |
|-------------|------------------------|-----|-----|----------|---------|-----------------------------------|------|---------------------|------|------------------------------------|--------|--------|-------------|
| | д: | Д: | Б: | r 1.2min | r3.4min | Кр | Cor | Grease | Oil | da max | Da max | ra max | Refer |
| | | | | | | | | | | | | | |
| NNC4920V | 100 | 140 | 40 | 1.1 | 194 | 194 | 400 | 950 | 2000 | 106.5 | 133.5 | 1 | 2 |
| NNCL4920V | 100 | 140 | 40 | 1.1 | 194 | 194 | 400 | 950 | 2000 | 106.5 | 133.5 | 1 | 2 |
| NNCF4920V | 100 | 140 | 40 | 1.1 | 194 | 194 | 400 | 950 | 2000 | 106.5 | 133.5 | 1 | 2 |
| NNCF5020V | 100 | 150 | 67 | 1.5 | 391 | 391 | 680 | 950 | 2000 | 108 | 142 | 1.5 | 4.05 |
| NNC4922V | 110 | 150 | 40 | 1.1 | 201 | 201 | 430 | 900 | 1900 | 116.5 | 143.5 | 1 | 2.15 |
| NNCL4922V | 110 | 150 | 40 | 1.1 | 201 | 201 | 430 | 900 | 1900 | 116.5 | 143.5 | 1 | 2.15 |
| NNCF4922V | 110 | 150 | 40 | 1.1 | 201 | 201 | 430 | 900 | 1900 | 116.5 | 143.5 | 1 | 2.15 |
| NNCF5022V | 110 | 170 | 80 | 2 | 528 | 528 | 930 | 850 | 1800 | 119 | 161 | 2 | 6.6 |
| NNCF4924V | 120 | 165 | 45 | 1.1 | 224 | 224 | 480 | 800 | 1700 | 126.5 | 158.5 | 1 | 2.9 |
| NNC4924V | 120 | 165 | 45 | 1.1 | 224 | 224 | 480 | 800 | 1700 | 126.5 | 158.5 | 1 | 2.9 |
| NNCL4924V | 120 | 165 | 45 | 1.1 | 224 | 224 | 480 | 800 | 1700 | 126.5 | 158.5 | 1 | 2.9 |
| NNCF5024V | 120 | 180 | 80 | 2 | 561 | 561 | 1020 | 800 | 1700 | 129 | 171 | 2 | 7.1 |
| NNC4926V | 130 | 180 | 50 | 1.5 | 255 | 255 | 530 | 750 | 1600 | 138 | 172 | 1.5 | 3.9 |
| NNCL4926V | 130 | 180 | 50 | 1.5 | 255 | 255 | 530 | 750 | 1600 | 138 | 172 | 1.5 | 3.9 |
| NNCF4926V | 130 | 180 | 50 | 1.5 | 255 | 255 | 530 | 750 | 1600 | 138 | 172 | 1.5 | 3.91 |
| NNCF5026V | 130 | 200 | 95 | 2 | 704 | 704 | 1370 | 700 | 1500 | 139 | 191 | 2 | 11 |
| NNC4928V | 140 | 190 | 50 | 1.5 | 264 | 264 | 570 | 700 | 1500 | 148 | 182 | 1.5 | 4.15 |
| NNCL4928V | 140 | 190 | 50 | 1.5 | 264 | 264 | 570 | 700 | 1500 | 148 | 182 | 1.5 | 4.15 |
| NNCF4928V | 140 | 190 | 50 | 1.5 | 264 | 264 | 570 | 700 | 1500 | 148 | 182 | 1.5 | 4.16 |
| NNCF5028CV | 140 | 210 | 95 | 2 | 737 | 737 | 1460 | 670 | 1400 | 149 | 201 | 2 | 11.5 |
| NNC4830V | 150 | 190 | 40 | 1.1 | 233 | 233 | 585 | 700 | 1500 | 156.5 | 183.5 | 1 | 2.9 |
| NNCL4830V | 150 | 190 | 40 | 1.1 | 233 | 233 | 585 | 700 | 1500 | 156.5 | 183.5 | 1 | 2.9 |
| NNC4930V | 150 | 210 | 60 | 2 | 380 | 380 | 850 | 670 | 1400 | 159 | 201 | 2 | 6.7 |
| NNCL4930V | 150 | 210 | 60 | 2 | 380 | 380 | 850 | 670 | 1400 | 159 | 201 | 2 | 6.7 |
| NNCF4930V | 150 | 210 | 60 | 2 | 380 | 380 | 850 | 670 | 1400 | 159 | 201 | 2 | 6.71 |
| NNCF5030V | 150 | 225 | 100 | 2.1 | 842 | 842 | 1660 | 630 | 1300 | 161 | 214 | 2 | 14 |
| NNCF4832V | 160 | 200 | 40 | 1.1 | 242 | 242 | 620 | 670 | 1400 | 166.5 | 193.5 | 1 | 3.05 |
| NNC4832V | 160 | 200 | 40 | 1.1 | 242 | 242 | 620 | 670 | 1400 | 166.5 | 193.5 | 1 | 3.05 |
| NNCL4832V | 160 | 200 | 40 | 1.1 | 242 | 242 | 620 | 670 | 1400 | 166.5 | 193.5 | 1 | 3.05 |
| NNCF4932V | 160 | 220 | 60 | 2 | 396 | 396 | 900 | 630 | 1300 | 169 | 211 | 2 | 7 |