

SS6900 Series

№ подшипника	Размеры (мм)				Ball Complement	Maximum speed (r/min)		Масса Kg/pcs
	Д:	д:	Б:	NO		Grease	Oil	
S 693	8	3	3	6	1.588	54000	63000	0.0006
S 694	11	4	4	7	2	45000	52000	0.0017
S 695	13	5	4	8	2	34000	43000	0.0023
S 696	15	6	5	8	2.381	32000	40000	0.0036
S 697	17	7	5	9	2.381	30000	38000	0.005
S 698	19	8	6	7	3.5	28000	36000	0.0076
S 699	20	9	6	9	2.381	27000	34000	0.0085
S 6900	22	10	6	12	2.381	25000	32000	0.009
S 6901	24	12	6	9	3.5	20000	28000	0.011
S 6902	28	15	7	10	3.969	19000	26000	0.016
S 6903	30	17	7	11	3.969	18000	24000	0.018
S 6904	37	20	9	11	4.763	17000	22000	0.036
S 6905	42	25	9	13	4.763	14000	18000	0.042
S 6906	47	30	9	14	4.763	12000	16000	0.048
S 6907	55	35	10	14	5.556	10000	14000	0.074
S 6908	62	40	12	14	6.747	8000	12000	0.11
S 6909	68	45	12	15	6.747	9000	11000	0.128
S 6910	72	50	12	16	6.747	8500	10000	0.132
S 6911	80	55	13	17	6.747	8000	9500	0.177
S 6912	85	60	13	18	6.747	7500	9000	0.191