

Single Row Cylindrical Roller Bearings

Bearing NO.		Граничные размеры (мм)						Номинальная грузоподъемность (кН)		Limiting speed (rpm)		Abutment and fillet dimensions (mm)						Weight (kg)		
New	Old	д:	Д:	Б:	r	1.2min	r ³ / _{min} ⁴	Fw	Ew	Кр	Cor	Grease	Oil	da min	db min	Da max	Db max	ra max	rb max	Refer
N220M	2220	100	180	34	2.1	2.1			160	190	260	3200	3800	114			166	2	2	3.45
NJ220EM		100	180	34	2.1	2.1	119			190	260	3200	3800		114	169		2	2	3.9
NF220M	12220	100	180	34	2.1	2.1			160	190	260	3200	3800	114			166	2	2	3.55
NU220M	32220	100	180	34	2.1	2.1	120			190	260	3200	3800		114	169		2	2	5.2
NJ220EM	42220	100	180	34	2.1	2.1	119			190	260	3200	3800		114	169		2	2	3.9
NU2220M	32520	100	180	46	2.1	2.1	120			260	390	3200	3800		114	169		2	2	5.2
NU320EM	32320EH	100	215	47	3	3	127.5			380	470	2400	3000		116	202		2.5	2.5	8.35
N320EM	2320EH	100	215	47	3	3		191.5		380	470	2400	3000	116			197	2.5	2.5	9.67
N2320M	2620	100	215	73	3	3		185.5		440	630	2400	3000	116			197	2.5	2.5	13.1
NU2320M	32620	100	215	73	3	3	129.5			440	630	2400	3000		116	197		2.5	2.5	13.2
NJ2320M	42620	100	215	73	3	3	129.5			440	630	2400	3000		116	197		2.5	2.5	13.5
NF1021M	12121	105	160	26	2	1.1	119.5	145.5		120	176	4000	4800		114	150		2	1	1.93
N1021M	2121	105	160	26	2	1.1		145.5		120	176	4000	4800	117			150	2	1	1.82
N221M	2221	105	190	36	2.1	2.1		168.8		210	290	3000	3600	119			175	2	2	4.33
NJ221M	42221	105	190	36	2.1	2.1	126.8			210	290	3000	3600		121	179		2	2	4.34
N321EM	2321EH	105	225	49	3	3		201		420	550	2200	2800	121			203	2.5	2.5	10.5
NU321EM	32321EH	105	225	49	3	3	133			420	550	2200	2800		121	212		2.5	2.5	10.6
N421M	2421	105	260	60	4	4		220.5		550	700	2200	2800	121			224	3	3	17.2
N1022M	2122	110	170	28	2	1.1		155		148	203	3800	4500	122			160			2.31
NU1022M	32122	110	170	28	2	1.1	125			148	203	3800	4500		119	157		2	1	2.32
NJ1022M	42122	110	170	28	2	1.1	125			148	203	3800	4500		119	157		2	1	2.39
N222M	2222	110	200	38	2.1	2.1		178.5		255	340	2800	3400	124			185	2	2	5.02
NU222M	32222	110	200	38	2.1	2.1	132.5			255	340	2800	3400		124	185		2	2	5.05
NJ222M	42222	110	200	38	2.1	2.1	132.5			255	340	2800	3400		124	185		2	2	5.1
NU2222EC	32522	110	200	53			132			380	520	2800	3400		124	185		2	2	7.73
N322EM	2322EH	110	240	50	3	3		211		430	540	2000	2600	126			227	2.5	2.5	11.4
NU322M	32322	110	240	50	3	3	143	207		400	525	2000	2600		126	222		2.5	2.5	11.6
NJ322M	42322	110	240	50	3	3	143	207		400	525	2000	2600		126	222		2.5	2.5	11.8
NU2322EM	32622EH	110	240	80	3	3	143			620	800	2000	2600		126	222		2.5	2.5	18.3
N422M	2422	110	280	65	4	4		235		580	735	2000	2600	130			252	3	3	21.8