

Tapered roller thrust bearing TTSP series

No Oil Holes In Retainer		Oil Holes In Retainer		Dimensions(mm/in.)				Steering Pivot Rating(N/lbf)	Bearing Weight(kg/lbs.)	Remarks
No Oil Holes In Retainer	Oil Holes In Retainer	Fig.	Fig.	д:	Д:	Т	R			
T63	T63W	A	A	16.129	41.275	12.7	0.8	11100	0.08	
T63		A		0.635	1.625	0.5	0.03	2500	0.18	
T76	T76W	A	A	19.304	41.275	13.487	0.8	11100	0.08	
T76		A		0.76	1.625	0.531	0.03	2500	0.18	
T77	T77W	A	A	19.304	41.275	12.7	0.8	11100	0.07	
T77		A		0.76	1.625	0.5	0.03	2500	0.15	
T82	T82W	A	A	20.879	41.275	13.487	0.8	11100	0.07	
T82		A		0.822	1.625	0.531	0.03	2500	0.15	
T86		A		20.257	39.688	14.288	1.3	10700	0.07	
T86		A		0.7975	1.5625	0.5625	0.05	2400	0.15	
T88	T88W	A	A	22.479	48.021	15.088	0.8	17300	0.11	
T88		A		0.885	1.8906	0.594	0.03	3890	0.24	
T89		A		22.479	48.021	15.875	0.8	17350	0.12	
T89		A		0.885	1.8906	0.625	0.03	3900	0.26	
T92		B		23.825	44.958	13.487	0.8	11950	**	T92 has two bores, other bore = 24.054 mm (0.9470)
T92		B		0.938	1.77	0.531	0.03	2690	0	
T93		A		24.054	44.958	13.487	0.8	11950	0.09	
T93		A		0.947	1.77	0.531	0.03	2690	0.2	
T94	T94W	A	A	24.054	48.021	15.088	0.8	17350	0.11	
T94		A		0.947	1.8906	0.594	0.03	3900	0.24	
T95	T95W	A	A	24.13	50.8	15.875	0.8	18600	0.13	
T95		A		0.95	2	0.625	0.03	4200	0.29	
T101	T101W	A	A	25.654	50.8	15.875	0.8	18600	0.13	

Tapered roller thrust bearing TTSP series

T101		A	1.01	2	0.625	0.03	4200	0.29	
T101X		A	25.146	50.8	15.875	0.8	18600	**	T101X has two bores, other bore = 24.654 mm (1.010
T101X		A	0.99	2	0.625	0.03	4200	0	
T102R		A	25.654	50.8	16.916	0.8	18600	**	T102 has extended retainer. Contact Timken engineer
T102R		A	1.01	2	0.666	0.03	4200	0	
T104	T104W	A	26.289	50.8	15.875	0.8	18600	0.13	
T104		A	1.035	2	0.625	0.03	4200	0.29	